

GEHL®

M100 EXCAVATOR



SPECIFICATIONS		M100
DRIVELINE	Engine Model	4TNV98CT-VBV
	Displacement	202.5 inches ³
	Rated Speed	2,100 rpm
	Engine Output - Gross	72 hp
DIMENSIONS	Transport Length	21'4"
	Transport Height - Maximum	9'3"
	Overall Width	7'7"
	Tail Swing Radius	4'4"
	Ground Level Reach - Mono Boom	24'3"
	Dump Height - Mono Boom	16'10"
	Dig Depth - Mono Boom	14'10"
	Boom Swing - Left/Right	60° / 60°
PERFORMANCE	Travel Speed - High/Low	2.7 mph / 1.6 mph
	Dipper Breakout	9,500 lbf
	Bucket Breakout	12,216 lbf
	End Lift - Maximum Reach	4,079 lbs.
	Operating Weight	21,550 lbs.



- ✓ Minimal tail swing design
- ✓ 14'0" dig depth and 60 degree boom swing for easy foundation digging
- ✓ Deluxe, ergonomic operator's station with choice of control pattern, ISO or SAE
- ✓ Easy to use joystick controls
- ✓ Large engine hood opens for easy service access



Gehl reserves the right to add improvements or make changes in features and specifications at any time without notice or obligation.

Gehl reminds users to read and understand the operator's manual before operating any equipment. Also, make sure all safety devices and shields are in place and functioning properly.